

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.



MODEL : PPS-125-27V

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 150 mVp-p (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	V1: 14 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 25.65 V~28.35V (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	21.58V~31.63V/ 230 VAC 21.58V~31.63V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: +1 %~ -1 % (Max)	I/P: 264 VAC / 100 VAC O/P:FULL/ 0 % LOAD Ta:25°C	V1: 0.03 %~ -0.03 %	P
4	LINE REGULATION	V1: +0.5%~ -0.5 % (Max)	I/P: 264 VAC ~ 100 VAC O/P:FULL LOAD Ta:25°C	V1:0 %~ 0.03 %	P
5	LOAD REGULATION	V1: +1 %~ -1 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.03 %~ -0.03 %	P
6	SET UP TIME	230 VAC/ 1000 ms (Max) 115 VAC/ 2000 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 465 ms 115 VAC/ 712 ms	P
7	RISE TIME	230 VAC/ 30 ms (Max) 115 VAC/ 30 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 23ms 115 VAC/ 23 ms	P
8	HOLD UP TIME	230 VAC/ 20 ms (Min) 115 VAC/ 20 ms (Min)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 34ms 115 VAC/ 34ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
10	DYNAMIC LOAD	V1: 2700 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	107 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	264 VAC~ 90 VAC (Typ)	I/P:TESTING O/P:FULL LOAD Ta:25°C	67V~ 264 V	P
			I/P: LOW-LINE-3V= 87 V HIGH-LINE+15%= 300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST:OK	
2	INPUT FREQUENCY RANGE	47 HZ ~ 63 HZ (Typ) NO DAMAGE OSC	I/P: 264 VAC ~ 100 VAC O/P:FULL-MIN LOAD Ta:25°C	TEST:OK	P
3	POWER FACTOR	0.93/ 230 VAC(TYP) 0.98/ 115 VAC(TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	PF=0.97 / 230 VAC PF=1 / 115 VAC	P
4	EFFICIENCY	83 % (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	83.5 %	P
5	INPUT CURRENT	230 V/ 0.75 A (Max) 115 V/ 1.7 A (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I =0.57A/ 230 VAC I =1.14A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 40 A (Max) COLD START	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	I =19.4 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 2 mA / 240 VAC	I/P:254 VAC O/P:Min LOAD Ta:25°C	L-FG: 0.92 mA N-FG:0.82 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	130 %~ 160 %(Typ)	I/P: 230 VAC I/P: 115 VAC O/P: TESTING Ta:25°C	138 %/ 230 VAC 131 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1: 31.05 V~ 36.45 V(Typ)	I/P: 230 VAC I/P: 115 VAC O/P: MIN LOAD Ta:25°C	33.3V/ 230 VAC 33.3V/ 115 VAC Hiccup Model	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT	
1	TEMPERATURE RISE TEST	MODEL : PPS-125-24 WITH FAN 17.8CFM 1. ROOM AMBIENT BURN-IN : 1 HRS I/P: 230 VAC O/P: 125% LOAD Ta= 26.7°C 2. HIGH AMBIENT BURN-IN : HRS I/P: 230 VAC O/P: 125% LOAD Ta= 49.8°C			P	
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 149% LOAD with FAN Ta:25°C	TEST : OK	P	
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 125 % LOAD with FAN Ta= -20 °C	TEST : OK	P	
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P: 272 VAC O/P:125% LOAD with FAN Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK	P	
5	TEMPERATURE COEFFICIENT	± 0.05 %(0~50°C)	I/P: 230 VAC O/P:125% LOAD with FAN	+0.004 %(0~50°C)	P	
6	VIBRATION TEST	1 Carton & 1 Set Operating at I/P: (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C	VAC NO LOAD	TEST :	N/A	

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 1.3 mA I/P-FG: 5.9 mA O/P-FG: 0.28 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 1.33 GΩ I/P-FG: 3.29 GΩ O/P-FG: 1.62G Ω NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : R50038987 UL: File NO : E183223			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N :1KV L,N-PE:2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				



M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C102 IS THE MOST CRITICAL COMPONENT WITH FAN I/P: 230 VAC O/P:125% LOAD Ta=25 °C LIFE TIME=592491 HRS I/P: 230 VAC O/P:125% LOAD Ta=50 °C LIFE TIME=110700 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 111.7K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 2 Rated 2SK2850 : 900 V 6 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 464 V (2) 652V (3) 884 V	P
2	Diode Peak Voltage	D17 Rated BYV32-200:200 V 20 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 131V (2) 149V (3) 149 V	P
3	Clamp Diode Peak Voltage	D4 Rated HER208 : 1K V 2 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load (2) Dynamic Load 90%Duty/1KHz Ta:25°C	(1) 644 V (2) 644 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2003/10/20	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2003/12/17	PRODUCT SAMPLE A311A38	PASS	VINCENT TSENG	MAX LIN

2003/7/14 A50-F023